


**Parallel Fast Recovery, 2x30A, 600V Diodes
In Isolated SOT227 Package**

APPLICATIONS

- Switch mode power supplies (SMPS) rectifiers
- Resonant applications
- Industrial drives



FEATURES

- Fast recovery
- Soft switching
- Low reverse recovery charge
- Low forward voltage drop
- Low leakage current
- Pb-free finished; **RoHS compliant**



MAXIMUM RATINGS (per Diode)

Parameter	Symbol	Value	Units
Repetitive peak reverse voltage	V_{RRM}	600	V
Continuous forward current $T_c=25^\circ C$ $T_c=85^\circ C$	I_F	50 30	A
Surge non-repetitive forward current $T_j= 25^\circ C$, $t_p = 10ms$, Sine halfwave	I_{FSM}	117	
Maximum repetitive forward current $T_c=25^\circ C$, t_p limited by T_{jmax} , $D=0.5$	I_{FRM}	81	
Soldering temperature Wave soldering, 1.6mm (0.063 in.) from case for 10s	T_s	260	$^\circ C$
Operating junction and storage temperature	T_j , T_{stg}	-55... +150	

Thermal and Isolation Characteristics


Parameter	Symbol	Max. Value	Units
Characteristics			
Thermal resistance, junction to case, per Diode	R_{thJC}	1.365	$^\circ C/W$
Isolation voltage, RMS (measured between terminals and mounting base, 50-60 Hz, for 1-3 seconds)	V_{iso}	3000	V

Electrical Characteristics (per Diode), at $T_j = 25^\circ C$, unless otherwise specified

Parameter	Symbol	Value			Unit
		Min.	Typ.	Max.	
Static Characteristics					
Reverse leakage current $V_R = 600V$	I_R	-	-	50 250	μA
Forward voltage drop $I_F = 30A$	V_F	-	1.5 1.5	2.0 -	V
$I_F = 30A$, $T_j = 150^\circ C$					

Electrical Characteristics (per Diode), at $T_j = 25^\circ\text{C}$, unless otherwise specified

Parameter	Symbol	Value			Unit
		Min.	Typ.	Max.	
Dynamic Characteristics					
Reverse recovery time $V_R = 400\text{V}$, $I_F = 30\text{A}$, $dI_F/dt = 1000\text{A}/\mu\text{s}$, $T_j = 25^\circ\text{C}$ $V_R = 400\text{V}$, $I_F = 30\text{A}$, $dI_F/dt = 1000\text{A}/\mu\text{s}$, $T_j = 125^\circ\text{C}$ $V_R = 400\text{V}$, $I_F = 30\text{A}$, $dI_F/dt = 1000\text{A}/\mu\text{s}$, $T_j = 150^\circ\text{C}$	t_{rr}	- - -	126 171 178	- - -	ns
Maximum reverse recovery current $V_R = 400\text{V}$, $I_F = 30\text{A}$, $dI_F/dt = 1000\text{A}/\mu\text{s}$, $T_j = 25^\circ\text{C}$ $V_R = 400\text{V}$, $I_F = 30\text{A}$, $dI_F/dt = 1000\text{A}/\mu\text{s}$, $T_j = 125^\circ\text{C}$ $V_R = 400\text{V}$, $I_F = 30\text{A}$, $dI_F/dt = 1000\text{A}/\mu\text{s}$, $T_j = 150^\circ\text{C}$	I_{rrm}	- - -	19 22 24	- - -	A
Reverse recovery charge $V_R = 400\text{V}$, $I_F = 30\text{A}$, $dI_F/dt = 1000\text{A}/\mu\text{s}$, $T_j = 25^\circ\text{C}$ $V_R = 400\text{V}$, $I_F = 30\text{A}$, $dI_F/dt = 1000\text{A}/\mu\text{s}$, $T_j = 125^\circ\text{C}$ $V_R = 400\text{V}$, $I_F = 30\text{A}$, $dI_F/dt = 1000\text{A}/\mu\text{s}$, $T_j = 150^\circ\text{C}$	Q_{rr}	- - -	1100 1950 2150	- - -	nC

Package Outline Drawing

Disclaimer

These specifications may not be considered as a guarantee of components characteristics. Components have to be tested depending on intended application as adjustments may be necessary. The use of **iQXPRZ Power Inc.** components in life support appliances and systems are subject to written approval of **iQXPRZ Power Inc.**